



Maxim > Design Support > Technical Documents > Tutorials > 1-Wire® Devices > APP 3438

Maxim > Design Support > Technical Documents > Tutorials > General Engineering Topics > APP 3438

Keywords: 1-wire, comparison, compare, serial, bus, networks, i2c, smbus, spi, microwire, plus, microwire/plus, m-bus, en1434, can, iso11898, lin

TUTORIAL 3438

Serial Digital Data Networks

By: Bernhard Linke, Principal Member Technical Staff
Jan 26, 2005

Abstract: This table provides top-level characteristics for serial interface standards by which two or more digital devices can be connected for communication. Design engineers can use the table to compare interface options for their application based on the design constraints like number of signal lines, network size, speed, distance, noise immunity, fault tolerance and reliability.

Dallas Semiconductor offers 1-Wire® serial protocol to designers interested in implementing a low-cost, minimal contact interface. A key benefit provided with this low-cost, master/slave architecture is the delivery of slave-device power on the same line used for digital communication. A 1-Wire master can easily be implemented on a microcontroller unit (MCU) with only a single I/O pin by using software. Bridge chips for I²C*, UART serial (RS-232), and USB-to-1-Wire are also available that off-load host-side 1-Wire protocol implementation and provide optimized 1-Wire waveform characteristics.

	1-Wire	I ² C*	SMBus™	SPI™	MicroWire/PLUS™	M-Bus (EN1434)	CAN (ISO11898)	LIN Bus
Network Concept	single master, multiple slaves	multiple masters, multiple slaves	multiple masters, multiple slaves	single master, multiple slaves	single master, multiple slaves	single master, multiple slaves	multiple masters, multiple slaves	single master, multiple slaves
Number of Signal Lines	1 (IO)	2, (SCL, SDA)	2, (SMBCLK, SMBDAT)	4, (active-low CS, SI, SO, SCK)	4, (active-low CS, DI, DO, SK)	2 (lines can be swapped)	2 (CAN_H, CAN_L, terminated)	1 (LIN)
Optional signals	N/A	N/A	SMBSUS#, SMBALERT#	N/A	N/A	N/A	2nd GND, Power, Shield	N/A
Network Size	Up to 300 m (with suitable master circuit)	Limited by max. 400pF bus capacitance requirement	Limited by max. 400pF bus capacitance requirement	N/A (circuit board level)	N/A (circuit board level)	Max. 350m per segment of max. 250 slaves; max. 180nF	40m @1M bps/1000m @ 50k bps (example)	Up to 40m, max. 10nF total load
Network Interface	open drain, resistive or active master pull-up	open drain, resistive or active master pull-up	open drain, resistive or active master pull-up	Push-pull with tristate	Push-pull with tristate	M to S: voltage drive S to M: current load	Differential open drain/source or open coll./emitter	open drain, resistive master pull-up
Network Voltage	From 2.8 to 6.0 V, device specific	From 1.8 to 5.5V, device specific	2.7V to 5.5V	From 1.8V to 5.5V, device specific	From 1.8V to 5.5V, device specific	~40V	V _{DD} -V _D (diode drop); ~4.5V max.	8 to 18V
		Fixed level:		V _{DD} -related	Fixed level: <0.8V,	Master to	Differential:	V _{DD} -related level: <20%,

Logic Thresholds	Vary with network voltage	>1.5V, >3.0 V V_{DD} -related level: <30%, >70% of V_{DD}	<0.8V, >2.1V	level: <20% (30%), >70% of V_{DD} (inconsistent)	>2.0V; V_{DD} -related level: <20% (30%), >70% (80%) of V_{DD} (inconsistent)	slave: 24V, 36V nominal Slave to master: <1.5mA, >11mA	<50mV (recessive), >1.5V (dominant); driver specification	>80% of V_{DD} (driver spec.) <40%, >60% of V_{DD} (receiver spec.)
Transmission	LS bit first, half-duplex	MS bit first plus Acknowledge bit, half-duplex	MS bit first plus Acknowledge bit, half-duplex	MS bit first, full-duplex	MS bit first, full-duplex	LS bit first, half-duplex, acknowledge response	MS bit first, half-duplex	LS bit first, half-duplex
Address Format	56 bits	7 bits, (10 bits defined but not implemented)	7 bits, (10 bits defined but not implemented)	N/A	N/A	8 bits (primary address), 64 bits (secondary address)	Message identifier 11 bits (standard format), 29 bits (extended format)	Message identifier 8 bits, including 2 parity bits
Network Inventory	Automatic, supports dynamic topology change	N/A; slave addresses hard-coded in firmware	ARP, Address Resolution Protocol (Rev. 2.0 only)	N/A; slave select (active-low CS) hard-coded in firmware	N/A; slave select (active-low CS) hard-coded in firmware	Automatic	N/A; message-based protocol, not address based	N/A; message-based protocol, not address based
Gross Data Rate	Standard: ~0 to 16.3k bps Overdrive: ~0 to 142k bps)	Standard: ~0 to 100k bps; Fast: ~0 to 400k bps; High-Speed: ~0 to 3.4M bps	10k to 100k bps	~0 to ~10 M bps (device specific)	~0 to ~5 M bps (device specific)	300, 2400, 9600 bps	~0 to 1M bps	~1k to ~20k bps
Access Time	Standard: ~ 5.4ms Overdrive: ~0.6ms (at maximum speed)	Standard: ~95µs Fast: ~23µs (at maximum speed)	~95µs @ 100k bps	N/A	N/A	Primary address, 2400 bps: 13.75ms (short frame), 27.5ms (long frame)	At 1M bps 19µs (standard) or 39µs (extended) from start of frame to 1st data bit	At 20k bps 1.7ms from start of frame to 1st data bit
Data Protection	8-bit and 16-bit CRC	N/A	PEC Packet Error Code (Rev. 1.1, 2.0)	N/A	N/A	Even parity, check sum, frames	15-bit CRC, frames, frame acknowledge	Check sum, frames
Collision Detection	Yes, through non-matching CRC	Yes (multi-master operation only)	Yes (Rev. 2.0 only)	N/A	N/A	Yes ("medium" and "strong" collisions)	Yes: CSMA/CD	Yes, through check sum
Slave supply	Parasitic (typical), V_{DD} (exception)	V_{DD} only	V_{DD} only	V_{DD} only	V_{DD} only	Parasitic and/or local supply	V_{DD} only, local or remote source	Parasitic only

1-Wire is a registered trademark of Maxim Integrated Products, Inc.
MICROWIRE PLUS is a trademark of National Semiconductor Corporation.

Related Parts

[DS2401](#) Silicon Serial Number [Free Samples](#)

[DS2408](#) 1-Wire 8-Channel Addressable Switch [Free Samples](#)

DS2431	1024-Bit 1-Wire EEPROM	Free Samples
DS2432	1Kb Protected 1-Wire EEPROM with SHA-1 Engine	Free Samples
DS2480B	Serial to 1-Wire Line Driver	Free Samples
DS2490	USB to 1-Wire Bridge Chip	
DS2502	1Kb Add-Only Memory	Free Samples

More Information

For Technical Support: <http://www.maximintegrated.com/support>

For Samples: <http://www.maximintegrated.com/samples>

Other Questions and Comments: <http://www.maximintegrated.com/contact>

Application Note 3438: <http://www.maximintegrated.com/an3438>

TUTORIAL 3438, AN3438, AN 3438, APP3438, Appnote3438, Appnote 3438

Copyright © by Maxim Integrated Products

Additional Legal Notices: <http://www.maximintegrated.com/legal>